



Design and Implementation of Solar Energy Based Thermoelectric Generator Using Parabolic Reflector

B.Christyjuliet,

PG scholar, Dept. of EEE, Kalaignar Karunanidhi Institute of Technology, Coimbatore-402.

christy.smily@gmail.com

Abstract - The applications of solar dish and thermoelectric generator have the research potential as green and clean energy generation from solar thermal route. In this paper, an attempt has been made to conduct an experimental study on small scale solar parabolic dish thermoelectric generator. The solar parabolic dish collector is fabricated using polished aluminum sheet as concentrator surface. Thermoelectric generator consists of commercial thermoelectric modules embedded between the receiver plate and aluminium heat sink which is placed on the focal plane of manual tracking parabolic dish collector. The concentrated solar radiation and aluminium sink is the driving potential to generate electricity, various operating parameters like receiver plate temperature, power output and conversion efficiency with respect to solar radiation are studied. It is found that the receiver plate temperature is significantly affecting the power output. Also, in this study it is identified to reuse the unused dish antenna for solar collector and coupled with commercial thermoelectric module is simple fabrication method easy to adopt in the rural techno craft for small scale power generator to meet the isolated energy demands.

Keywords- Solar Parabolic Dish Collector; Thermoelectric Generator; Power Output; Heat Sink

I. INTRODUCTION

Green and clean energy providing technology main focuses on the world problems of greenhouse gas emission and energy shortage. Solar energy is attractive to substitute for the conventional fuels due to its abundant availability, clean and safe source of energy in its conversion processes. Thermoelectric generator (TEG) is solid state direct energy conversion device, it is simple in construction and easy to fabricate by sintering process. It has many advantages such as highly reliable, having no moving parts and environmentally friendly, when compared with conventional power generators. There have been considerable emphases on the development of small capacity TEGs for variety of applications such as aerospace, military, medical, and self-sufficient energy system over the last few years. More recently, there is a growing interest for standalone power generation system combining TEG using concentrating and non-concentrating type solar thermal collector [2]. Thermodynamic analysis of solar parabolic dish thermoelectric power generator is studied for analyze the design parameters and operating parameters and found that energy loss found maximum at thermoelectric generator due to its lower figure merit value of thermoelectric generator [6].

In the case of TEG for combination of solar thermal collector for power generation, there have been many conceptual designs of power conversion system which are potentially capable of obtaining application in this area [4], [5]. These designs involve the consideration of the maximum power output and conversion efficiency with different thermoelectric heat exchanger. The performance evaluations of TEG have been theoretically carried out by modeling approach [1]. The results show that TEG promising options for waste heat recovery and solar thermal collectors. The economic viability of a TEG may be improved significantly when used for solar thermal collector that could reduce the device cost and increase the conversion efficiency of the device. Therefore, one of the more attractive options for solar dish collector is to construct the TEG device by incorporating the relatively simple water cooled heat sink with commercial thermoelectric modules. The developed TEG unit with commercial thermoelectric modules made of bismuth telluride alloys for an anticipated maximum generation of about 60-85 W. In this work an experimental investigation to be made on the solar parabolic dish thermoelectric generator for small scale power generation and its performance characteristic over the beam radiation to be made at Tiruchirappalli (Latitude 78.43E and Longitude 10.45N).

II. EXPERIMENTAL SETUP

The system consists of the thermoelectric modules, the heat sink device, the receiver plate, and manual tracking arrangement for the solar parabolic dish collector. The stainless steel box acts as heat sink and their flat surface having its surface area of 0.08 m^2 and sheet thickness of 2 mm which is opposite to the lid which is attached to cold side of thermoelectric modules. The cold water is circulated to the heat sink to maintain the cold side temperature at minimum; the cold water is drawn from the overhead tank. The flow rate of cold water is adjusted manually by the valve arrangement in order to maintain the constant outlet temperature of the water. So, we can maintain the mean temperature of water is considered as the heat sink temperature. The receiver plate is made aluminum sheet have 3 mm thickness, its surface area of 0.1 m^2 and its surface was coated with dull black paint to absorb the concentrated solar radiation from



concentrator, the receiver plate as heat sources is attached to the hot side of thermoelectric modules.

A. Solar Parabolic Dish Collector

The parabolic reflector is made of aluminum frame. The receiver plate was placed at the focus. A manual tracking mechanism arranged at the bottom of the dish helped to track the sun. The dish has the open mouth diameter of 3.56 m, focus of 1.11 m, height of 70 cm, and aperture angle of 69°. A rectangular sheet of thickness 0.3 mm, width 0.61 m, and length 1m was cut diagonally into two pieces. The reflector surfaces were made by 20 triangular pieces of aluminum sheet polished on one side, fixed on the aluminum rib by a set of bolts and nuts by keeping the polishing side facing the sun. The flat receiver plate made of aluminum sheet with 30 cm square in size with thickness of 3 mm to absorb the concentrated solar radiation from the PDC. The absorbed heat energy in the receiver plate is transmitted to the hot side of thermoelectric modules after the convection, radiation, and conduction losses. The receiver assembly, which comprises heat sources, thermoelectric modules and aluminium heat sink is attached to the cross base of two mild steel plates 5 mm thick and 32 mm long.

B. Thermoelectric Generator Unit

The TEG unit consists of the receiver plate made of aluminum sheet; thermoelectric module are made of bismuth telluride and the heat sink made of aluminium steel materials as shown in the pictorial view (Figure 1 and Figure 2).



Figure 1: The arrangement of TEG setup with parabolic reflector

A single thermoelectric modules with total rated power generation of 72 W is embedded between the receiver plate and the heat sink. Commercial thermoelectric modules having the dimension of 56 mm x 56 mm, a matrix of one hundred and twenty six thermoelectric couples (p-type and n-type), generate electric power of 14.7 W when the temperature of 230°C and 30°C and heat supplied is 350 W. Thermal grease is placed between all of the thermoelectric modules /receiver plate and heat sink interfaces in order to minimize the thermal contact resistance.



Figure 21 TEG setup below the heat sink

C. Instrumentation

Operating parameters such as receiver plate temperature, heat sink temperature and ambient temperature are measured by using K type thermocouples made chromel-alumel having an accuracy of $0.1^{\circ}C$ connected to the measuring points. Solar beam radiation is measured by the pyranometer instrument (Make: Energy and Environmental Ltd, Cochin) with an accuracy of 0.1% and the wind velocity is measured by the wind anemometer. The generated voltage, electrical current and connected electrical load of TEG is measured by using the digital multimeter, voltmeter and ammeter.

III. RESULTS AND DISCUSSION

Solar parabolic dish thermoelectric generator was tested at outdoor condition on clear sun days at in our college campus itself (Coimbatore, India). The main operating parameters like receiver plate temperatures, solar beam radiations and electrical powers (current x voltage) are recorded. The performances of the TEG are evaluated in terms of the electrical power output and the conversion efficiency from the following relations. The electrical power output from thermoelectric generator for connected load resistance and voltage generated between the two terminals is given by

$$P = \frac{V^2}{R_L} \quad (1)$$

$$h = \frac{P}{Q_h} \quad (2)$$

where P is Electrical power output from TEG, V is generated voltage from TEG, R_L is the connected electrical load, and Q_h is heat input to TEG from the solar parabolic dish collector which can be computed from the following relation,

$$Q_h = h_o C_R A_r I_b \quad (3)$$

Where h_o the optical efficiency of the solar dish collector, A_r is the surface area of the receiver plate. I_b is the beam radiation, and C_R is the concentration ratio. Experiments are conducted for a range of operating conditions as follows; the receiver plate temperature is varying between 350 K and 650 K and the mean temperature of heat sink 300 K to 310 K. The maximum uncertainty in the conversion efficiency is 6.7%. In addition, the relative heat loss from TEG is estimated to be approximately 3.5% or less based on the insulation conductivity and thickness. Experimental performance evaluation of the TEG system is carried out on the basis of data derived from tests.

The experiments were conducted on 21.5.2015. Figure 2 shows the variation of receiver plate temperature over the measured solar beam radiation. The receiver plate temperature obtained was maximum 602 K at the solar beam radiation of $950 W/m^2$. The minimum temperature of the receiver plate obtained was 375 K at solar beam radiation value of $430 W/m^2$. The following correlation with $R^2 = 0.98$ was obtained to compute the receiver plate temperature for any solar beam radiation that can be computed using the correlations developed from the experimental data,



$$T_p = 0.0002I_b^2 + 0.0231I_b + 324.14 \quad (4)$$




Figure 3: Receiver plate temperatures as function of solar beam radiation

The electrical power output from the solar parabolic dish thermoelectric power generator over the beam radiation is illustrated in Figure 3.




Figure 4: Maximum power output as function of solar beam radiation

The measured current and voltage for constant resistance of 4 Ω in terms of electrical power generation. The maximum power output of 68 W obtained when the solar beam radiation the maximum value at 950 W/m² with the receiver plate temperature of 602 K. The minimum power output of 11 W was obtained when the solar beam radiation value at reaches 430W/m² with the receiver plate temperature of 375 K. with R²=0.96 was electrical power output over the beam radiation, can be computed from the following model



$$P_{teg} = -0.0002 I_b^2 + 0.3304 I_b - 103.31 \quad (5)$$




Figure 5: Overall efficiency of solar parabolic dish thermoelectric generator as function of solar beam radiation

Figure 4 illustrates the overall efficiency of the solar parabolic dish thermoelectric power generator over the beam radiation values. The maximum efficiency of 0.78% was obtained when the solar beam radiation is maximum value at 950 W/m^2 . The minimum overall efficiency of 0.22% obtained when the solar beam radiation had the value of 431 W/m^2 . The overall efficiency of the solar parabolic dish thermoelectric power generator over the beam radiation can be computed from the following model 0.99. The generated power was stored in a battery and is used for lighting load like night lamp.

IV. CONCLUSION

The power generation from the combined system of solar parabolic dish collector and commercial thermoelectric modules was developed. The results of absorber plate temperature, power output and overall conversion efficiency are derived from the experimental investigation are reported for the different solar beam radiations. The performances of the systems are greatly affected by the heat sink temperature. Correlations for determining the plate temperature, electrical power output and overall conversion efficiency have been developed in terms of solar beam radiation. The experimental investigation shows that the generation of electricity from the low cost solar parabolic dish collector and commercial thermoelectric modules is a feasible option and also it is highly suitable for isolated energy demand where the conventional grid is not feasible or available.

REFERENCES

- [1] Douglas T. Crane and Gregory S. Jackson. 2004. Optimization of cross flow heat exchangers for thermoelectric waste heat recovery, *Energy Conversion and Management* 45: 1565–1582.
- [2] Ono K. and R. O. Suzuki. 1998. Thermoelectric power generation: converting low-grade heat into electricity. *Journal of the Minerals, Metals & Materials Society*. 50 (5): 12–31.
- [3] Rowe D. M. 1999. Thermoelectrics: an environmentally-friendly source of electrical power, *Renewable Energy*. 16: 1251–1256.
- [4] Suzuki, R. O., 2004. Mathematic simulation on power generation by roll cake type of thermoelectric double cylinders. *Journal of Power Sources*. 133: 277–285.
- [5] Suzuki, R. O., and Daisuke Tanaka. 2003. Mathematical simulation of thermoelectric power generation with the multi-panels. *Journal of Power Sources*. 122: 201–209.
- [6] Eswaramoorthy M and Shanmugam 2010 Thermodynamic analysis of solar parabolic dish thermoelectric generator *International Journal of Renewable Energy Technology*, 1 (3): 348-360.